

Polarex Pastel Hygienic PVC Wall Cladding

Technical Specification Sheet

Finish	Satin
Thickness	2.5mm
Size	24400mm x 1220mm 3050mm x 1220mm
Max Temp.	60°C
Weight	3.5kg per m ² (0.7lb ft ²)

Suitable Substrates

12.5mm plasterboard, mechanically fixed plywood, sand and cement rendering 1:3 with steel trowel finish, dust free good quality fair faced brick or blockwork, ceramic tiles which are securely bonded to substrate and degreased, 9mm (minimum) W.B.P resin bonded to substrate.

Method of Fixing

Sheets are fully bonded to suitable substrate with trowel applied Polarex 2-Part Adhesive.

Cutting

Fine toothed blade jigsaw or circular saw with fine TCT sawblade whilst sheet is supported.

Joints

Sheets can be sealed by hot welding providing a seamless finish or joined with matching PVC trims.

Between Sheets and Floor

Sheets can be overlaid or trim fixed to a vinyl flooring system.

Internal/External Corners

Polarex Pastel Hygienic PVC Cladding Sheets can be thermoformed to provide a seamless finish or joined using matching PVC External and Internal Corners.

Cleaning

Regular hot soapy water is sufficient for regular cleaning and a mild cleaning product is suitable. DO NOT USE abrasive cleaners. Steam Cleaning can be introduced to stubborn stains. Mild solvents may also be used but under 60°C and power hosed no closer than 600mm

Chemical Resistance

Resistant to a wide range of chemicals found within the medical, healthcare and food production industries.



Fire Ratings

UK – BS 476 Class 1/0
EU – EN13501 B-S3-D0
USA – ASTM E84 Class A
CAN – Can/UCL-S102.2 Tested

Warranty / Guarantees

Product 20 year warranty. Lifetime warranty on antimicrobial protection.

Storage

Sheets to be stored flat and left at ambient room temperature for 24 hours. Minimum temperature 13°C. Maximum Temperature 40°C. Avoid direct sunlight whilst storing.

Limitations of Use

Maximum temperature of 60°C. Sheets can NOT be used near naked flame. Full technical information and consultation available from our technical department.

Colours

Select as required – PC002 Grey Stone, PC003 Peppermint, PC004 Vanilla, PC005 Sky Blue, PC017 Chalk Tan, PC018 Cotton, PC020 Light Pistachio, PC021 Stone, PC025 Dusk, PC026 Stormy, PC027 Egg Shell, PC029 Duck Egg, PC030 Mallow, PC044 Sand



Polar Hygienic Finishes

Unit 10 Haverscroft Industrial Estate,
New Road
Attleborough,
Norfolk,
NR17 1YE